

# MC10E141, MC100E141

## 5V ECL 8-Bit Shift Register

### Description

The MC10E/100E141 is an 8-bit full-function shift register. The E141 performs serial/parallel in and serial/parallel out, shifting in either direction. The eight inputs  $D_0 - D_7$  accept parallel input data, while DL/DR accept serial input data for left/right shifting. The Qn outputs do not need to be terminated for the shift operation to function. To minimize noise and power, any Q output not used should be left unterminated.

The select pins, SEL0 and SEL1, select one of four modes of operation: Load, Hold, Shift Left, Shift Right, according to the Function Table.

Input data is accepted a set-up time before the positive clock edge. A HIGH on the Master Reset (MR) pin asynchronously resets all the registers to zero.

The 100 Series contains temperature compensation.


### Features

- 700 MHz Min. Shift Frequency
  - 8-Bit
  - Full-Function, Bi-Directional
  - Asynchronous Master Reset
  - Pin-Compatible with E241
  - PECL Mode Operating Range:  $V_{CC} = 4.2 \text{ V}$  to  $5.7 \text{ V}$  with  $V_{EE} = 0 \text{ V}$
  - NECL Mode Operating Range:  $V_{CC} = 0 \text{ V}$  with  $V_{EE} = -4.2 \text{ V}$  to  $-5.7 \text{ V}$
  - Internal Input  $50 \text{ k}\Omega$  Pulldown Resistors
  - ESD Protection: Human Body Model;  $> 2 \text{ kV}$ , Machine Model;  $> 200 \text{ V}$
  - Meets or Exceeds JEDEC Standard EIA/JESD78 IC Latchup Test
  - Moisture Sensitivity Level:
    - Pb = 1
    - Pb-Free = 3
- For Additional Information, see Application Note AND8003/D
- Flammability Rating: UL 94 V-0 @ 0.125 in, Oxygen Index: 28 to 34
  - Transistor Count = 565 devices
  - Pb-Free Packages are Available\*




**ON Semiconductor®**

<http://onsemi.com>



**PLCC-28  
FN SUFFIX  
CASE 776**

### MARKING DIAGRAM\*



|     |                     |
|-----|---------------------|
| xxx | = 10 or 100         |
| A   | = Assembly Location |
| WL  | = Wafer Lot         |
| YY  | = Year              |
| WW  | = Work Week         |
| G   | = Pb-Free Package   |


\*For additional marking information, refer to Application Note AND8002/D.

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# MC10E141, MC100E141



\* All  $V_{CC}$  and  $V_{CCO}$  pins are tied together on the die.  
 Warning: All  $V_{CC}$ ,  $V_{CCO}$ , and  $V_{EE}$  pins must be externally connected to Power Supply to guarantee proper operation.

**Figure 1. 28-Lead Pinout**


**Table 1. PIN DESCRIPTION**

| PIN                  | FUNCTION                  |
|----------------------|---------------------------|
| $D_0 - D_7$          | ECL Parallel Data Inputs  |
| DL, DR               | ECL Serial Data Inputs    |
| SEL0, SEL1           | ECL Mode Select In Inputs |
| CLK                  | ECL Clock                 |
| $Q_0 - Q_7$          | ECL Data Outputs          |
| MR                   | ECL Master Reset          |
| $V_{CC}$ , $V_{CCO}$ | Positive Supply*          |
| $V_{EE}$             | Negative Supply           |
| NC                   | No Connect                |

\*From  $V_{CC}$  pin to each  $V_{CCO}$  pin is an internal  $100\ \Omega$  resistor.

**Table 2. FUNCTION TABLE**

| SEL0 | SEL1 | FUNCTION                           |
|------|------|------------------------------------|
| L    | L    | Load                               |
| L    | H    | Shift Right ( $D_n$ to $D_{n+1}$ ) |
| H    | L    | Shift Left ( $D_n$ to $D_{n-1}$ )  |
| H    | H    | Hold                               |



**Figure 2. Logic Diagram**

**Table 3. EXPANDED FUNCTION TABLE**

| Function    | DL | DR | SEL0 | SEL1 | MR | CLK | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 | Q6 | Q7 |
|-------------|----|----|------|------|----|-----|----|----|----|----|----|----|----|----|
| Load        | X  | X  | L    | L    | L  | Z   | D0 | D1 | D2 | D3 | D4 | D5 | D6 | D7 |
| Shift Right | X  | L  | L    | H    | L  | Z   | L  | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 | Q6 |
|             | X  | H  | L    | H    | L  | Z   | H  | L  | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 |
| Shift Left  | L  | X  | H    | L    | L  | Z   | L  | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 | L  |
|             | H  | X  | H    | L    | L  | Z   | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 | L  | H  |
| Hold        | X  | X  | H    | H    | L  | Z   | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 | L  | H  |
|             | X  | X  | H    | H    | L  | Z   | Q0 | Q1 | Q2 | Q3 | Q4 | Q5 | L  | H  |
| Reset       | X  | X  | X    | X    | H  | X   | L  | L  | L  | L  | L  | L  | L  | L  |

# MC10E141, MC100E141

**Table 4. MAXIMUM RATINGS**

| Symbol           | Parameter                                          | Condition 1                                    | Condition 2                                                          | Rating                     | Unit         |
|------------------|----------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|----------------------------|--------------|
| V <sub>CC</sub>  | PECL Mode Power Supply                             | V <sub>EE</sub> = 0 V                          |                                                                      | 8                          | V            |
| V <sub>EE</sub>  | NECL Mode Power Supply                             | V <sub>CC</sub> = 0 V                          |                                                                      | –8                         | V            |
| V <sub>I</sub>   | PECL Mode Input Voltage<br>NECL Mode Input Voltage | V <sub>EE</sub> = 0 V<br>V <sub>CC</sub> = 0 V | V <sub>I</sub> ≤ V <sub>CC</sub><br>V <sub>I</sub> ≥ V <sub>EE</sub> | 6<br>–6                    | V<br>V       |
| I <sub>out</sub> | Output Current                                     | Continuous<br>Surge                            |                                                                      | 50<br>100                  | mA<br>mA     |
| T <sub>A</sub>   | Operating Temperature Range                        |                                                |                                                                      | 0 to +85                   | °C           |
| T <sub>stg</sub> | Storage Temperature Range                          |                                                |                                                                      | –65 to +150                | °C           |
| θ <sub>JA</sub>  | Thermal Resistance (Junction–to–Ambient)           | 0 lfpm<br>500 lfpm                             | PLCC–28<br>PLCC–28                                                   | 63.5<br>43.5               | °C/W<br>°C/W |
| θ <sub>JC</sub>  | Thermal Resistance (Junction–to–Case)              | Standard Board                                 | PLCC–28                                                              | 22 to 26                   | °C/W         |
| V <sub>EE</sub>  | PECL Operating Range<br>NECL Operating Range       |                                                |                                                                      | 4.2 to 5.7<br>–5.7 to –4.2 | V<br>V       |
| T <sub>sol</sub> | Wave Solder<br>Pb<br>Pb–Free                       |                                                |                                                                      | 265<br>265                 | °C           |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

**Table 5. 10E SERIES PECL DC CHARACTERISTICS** V<sub>CCx</sub> = 5.0 V; V<sub>EE</sub> = 0.0 V (Note 1)

| Symbol          | Characteristic               | 0°C  |      |      | 25°C |      |      | 85°C |      |      | Unit |
|-----------------|------------------------------|------|------|------|------|------|------|------|------|------|------|
|                 |                              | Min  | Typ  | Max  | Min  | Typ  | Max  | Min  | Typ  | Max  |      |
| I <sub>EE</sub> | Power Supply Current         |      | 131  | 181  |      | 131  | 181  |      | 131  | 181  | mA   |
| V <sub>OH</sub> | Output HIGH Voltage (Note 2) | 3980 | 4070 | 4160 | 4020 | 4105 | 4190 | 4090 | 4185 | 4280 | mV   |
| V <sub>OL</sub> | Output LOW Voltage (Note 2)  | 3050 | 3210 | 3370 | 3050 | 3210 | 3370 | 3050 | 3227 | 3405 | mV   |
| V <sub>IH</sub> | Input HIGH Voltage           | 3830 | 3995 | 4160 | 3870 | 4030 | 4190 | 3940 | 4110 | 4280 | mV   |
| V <sub>IL</sub> | Input LOW Voltage            | 3050 | 3285 | 3520 | 3050 | 3285 | 3520 | 3050 | 3302 | 3555 | mV   |
| I <sub>IH</sub> | Input HIGH Current           |      |      | 150  |      |      | 150  |      |      | 150  | μA   |
| I <sub>IL</sub> | Input LOW Current            | 0.5  | 0.3  |      | 0.5  | 0.25 |      | 0.3  | 0.2  |      | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfpm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

1. Input and output parameters vary 1:1 with V<sub>CC</sub>. V<sub>EE</sub> can vary –0.46 V / +0.06 V.
2. Outputs are terminated through a 50 Ω resistor to V<sub>CC</sub> – 2.0 V.

# MC10E141, MC100E141

**Table 6. 10E SERIES NECL DC CHARACTERISTICS**  $V_{CCx} = 0.0\text{ V}$ ;  $V_{EE} = -5.0\text{ V}$  (Note 3)

| Symbol   | Characteristic               | 0°C   |       |       | 25°C  |       |       | 85°C  |       |       | Unit |
|----------|------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|          |                              | Min   | Typ   | Max   | Min   | Typ   | Max   | Min   | Typ   | Max   |      |
| $I_{EE}$ | Power Supply Current         |       | 131   | 181   |       | 131   | 181   |       | 131   | 181   | mA   |
| $V_{OH}$ | Output HIGH Voltage (Note 4) | -1020 | -930  | -840  | -980  | -895  | -810  | -910  | -815  | -720  | mV   |
| $V_{OL}$ | Output LOW Voltage (Note 4)  | -1950 | -1790 | -1630 | -1950 | -1790 | -1630 | -1950 | -1773 | -1595 | mV   |
| $V_{IH}$ | Input HIGH Voltage           | -1170 | -1005 | -840  | -1130 | -970  | -810  | -1060 | -890  | -720  | mV   |
| $V_{IL}$ | Input LOW Voltage            | -1950 | -1715 | -1480 | -1950 | -1715 | -1480 | -1950 | -1698 | -1445 | mV   |
| $I_{IH}$ | Input HIGH Current           |       |       | 150   |       |       | 150   |       |       | 150   | μA   |
| $I_{IL}$ | Input LOW Current            | 0.5   | 0.3   |       | 0.5   | 0.065 |       | 0.3   | 0.2   |       | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

3. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary  $-0.46\text{ V} / +0.06\text{ V}$ .

4. Outputs are terminated through a  $50\ \Omega$  resistor to  $V_{CC} - 2.0\text{ V}$ .

**Table 7. 100E SERIES PECL DC CHARACTERISTICS**  $V_{CCx} = 5.0\text{ V}$ ;  $V_{EE} = 0.0\text{ V}$  (Note 5)

| Symbol   | Characteristic               | 0°C  |      |      | 25°C |      |      | 85°C |      |      | Unit |
|----------|------------------------------|------|------|------|------|------|------|------|------|------|------|
|          |                              | Min  | Typ  | Max  | Min  | Typ  | Max  | Min  | Typ  | Max  |      |
| $I_{EE}$ | Power Supply Current         |      | 131  | 181  |      | 131  | 181  |      | 151  | 181  | mA   |
| $V_{OH}$ | Output HIGH Voltage (Note 6) | 3975 | 4050 | 4120 | 3975 | 4050 | 4120 | 3975 | 4050 | 4120 | mV   |
| $V_{OL}$ | Output LOW Voltage (Note 6)  | 3190 | 3295 | 3380 | 3190 | 3255 | 3380 | 3190 | 3260 | 3380 | mV   |
| $V_{IH}$ | Input HIGH Voltage           | 3835 | 3975 | 4120 | 3835 | 3975 | 4120 | 3835 | 3975 | 4120 | mV   |
| $V_{IL}$ | Input LOW Voltage            | 3190 | 3355 | 3525 | 3190 | 3355 | 3525 | 3190 | 3355 | 3525 | mV   |
| $I_{IH}$ | Input HIGH Current           |      |      | 150  |      |      | 150  |      |      | 150  | μA   |
| $I_{IL}$ | Input LOW Current            | 0.5  | 0.3  |      | 0.5  | 0.25 |      | 0.5  | 0.2  |      | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

5. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary  $-0.46\text{ V} / +0.8\text{ V}$ .

6. Outputs are terminated through a  $50\ \Omega$  resistor to  $V_{CC} - 2.0\text{ V}$ .

**Table 8. 100E SERIES NECL DC CHARACTERISTICS**  $V_{CCx} = 0.0\text{ V}$ ;  $V_{EE} = -5.0\text{ V}$  (Note 7)

| Symbol   | Characteristic               | 0°C   |       |       | 25°C  |       |       | 85°C  |       |       | Unit |
|----------|------------------------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|------|
|          |                              | Min   | Typ   | Max   | Min   | Typ   | Max   | Min   | Typ   | Max   |      |
| $I_{EE}$ | Power Supply Current         |       | 131   | 181   |       | 131   | 181   |       | 151   | 181   | mA   |
| $V_{OH}$ | Output HIGH Voltage (Note 8) | -1025 | -950  | -880  | -1025 | -950  | -880  | -1025 | -950  | -880  | mV   |
| $V_{OL}$ | Output LOW Voltage (Note 8)  | -1810 | -1705 | -1620 | -1810 | -1745 | -1620 | -1810 | -1740 | -1620 | mV   |
| $V_{IH}$ | Input HIGH Voltage           | -1165 | -1025 | -880  | -1165 | -1025 | -880  | -1165 | -880  | -1025 | mV   |
| $V_{IL}$ | Input LOW Voltage            | -1810 | -1645 | -1475 | -1810 | -1645 | -1475 | -1810 | -1475 | -1645 | mV   |
| $I_{IH}$ | Input HIGH Current           |       |       | 150   |       |       | 150   |       |       | 150   | μA   |
| $I_{IL}$ | Input LOW Current            | 0.5   | 0.3   |       | 0.5   | 0.25  |       | 0.5   | 0.2   |       | μA   |

NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

7. Input and output parameters vary 1:1 with  $V_{CC}$ .  $V_{EE}$  can vary  $-0.46\text{ V} / +0.8\text{ V}$ .

8. Outputs are terminated through a  $50\ \Omega$  resistor to  $V_{CC} - 2.0\text{ V}$ .

# MC10E141, MC100E141

**Table 9. AC CHARACTERISTICS**  $V_{CCx} = 5.0\text{ V}$ ;  $V_{EE} = 0.0\text{ V}$  or  $V_{CCx} = 0.0\text{ V}$ ;  $V_{EE} = -5.0\text{ V}$  (Note 9)

| Symbol                               | Characteristic                           | 0°C               |                       |            | 25°C              |                       |            | 85°C              |                       |            | Unit |
|--------------------------------------|------------------------------------------|-------------------|-----------------------|------------|-------------------|-----------------------|------------|-------------------|-----------------------|------------|------|
|                                      |                                          | Min               | Typ                   | Max        | Min               | Typ                   | Max        | Min               | Typ                   | Max        |      |
| $f_{\text{SHIFT}}$                   | Max. Shift Frequency                     | 700               | 900                   |            | 700               | 900                   |            | 700               | 900                   |            | MHz  |
| $t_{\text{PLH}}$<br>$t_{\text{PHL}}$ | Propagation Delay To Output<br>Clk<br>MR | 625<br>600        | 750<br>725            | 975<br>975 | 625<br>600        | 750<br>725            | 975<br>975 | 625<br>600        | 750<br>725            | 975<br>975 | ps   |
| $t_s$                                | Setup Time<br>D<br>SEL0<br>SEL1          | 175<br>350<br>300 | 25<br>200<br>150      |            | 175<br>350<br>300 | 25<br>200<br>150      |            | 175<br>350<br>300 | 25<br>200<br>150      |            | ps   |
| $t_h$                                | Hold Time<br>D<br>SEL0<br>SEL1           | 200<br>100<br>100 | - 25<br>- 200<br>-150 |            | 200<br>100<br>100 | - 25<br>- 200<br>-150 |            | 200<br>100<br>100 | - 25<br>- 200<br>-150 |            | ps   |
| $t_{\text{RR}}$                      | Reset Recovery Time                      | 900               | 700                   |            | 900               | 700                   |            | 900               | 700                   |            | ps   |
| $t_{\text{PW}}$                      | Minimum Pulse Width<br>Clk, MR           | 400               |                       |            | 400               |                       |            | 400               |                       |            | ps   |
| $t_{\text{SKEW}}$                    | Within-Device Skew (Note 10)             |                   | 60                    |            |                   | 60                    |            |                   | 60                    |            | ps   |
| $t_{\text{JITTER}}$                  | Random Clock Jitter (RMS)                |                   | < 1                   |            |                   | < 1                   |            |                   | < 1                   |            | ps   |
| $t_r$<br>$t_f$                       | Rise/Fall Times<br>(20 - 80%)            | 300               | 525                   | 800        | 300               | 525                   | 800        | 300               | 525                   | 800        | ps   |


NOTE: Device will meet the specifications after thermal equilibrium has been established when mounted in a test socket or printed circuit board with maintained transverse airflow greater than 500 lfm. Electrical parameters are guaranteed only over the declared operating temperature range. Functional operation of the device exceeding these conditions is not implied. Device specification limit values are applied individually under normal operating conditions and not valid simultaneously.

9. 10 Series:  $V_{EE}$  can vary  $-0.46\text{ V} / +0.06\text{ V}$ .

100 Series:  $V_{EE}$  can vary  $-0.46\text{ V} / +0.8\text{ V}$ .

10. Within-device skew is defined as identical transitions on similar paths through a device.

## MC10E141, MC100E141



**Figure 3. Typical Termination for Output Driver and Device Evaluation**  
(See Application Note AND8020/D – Termination of ECL Logic Devices.)

### ORDERING INFORMATION

| Device         | Package              | Shipping <sup>†</sup> |
|----------------|----------------------|-----------------------|
| MC10E141FN     | PLCC-28              | 37 Units / Rail       |
| MC10E141FNG    | PLCC-28<br>(Pb-Free) | 37 Units / Rail       |
| MC10E141FNR2   | PLCC-28              | 500 / Tape & Reel     |
| MC10E141FNR2G  | PLCC-28<br>(Pb-Free) | 500 / Tape & Reel     |
| MC100E141FN    | PLCC-28              | 37 Units / Rail       |
| MC100E141FNG   | PLCC-28<br>(Pb-Free) | 37 Units / Rail       |
| MC100E141FNR2  | PLCC-28              | 500 / Tape & Reel     |
| MC100E141FNR2G | PLCC-28<br>(Pb-Free) | 500 / Tape & Reel     |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

### Resource Reference of Application Notes

- AN1405/D** – ECL Clock Distribution Techniques
- AN1406/D** – Designing with PECL (ECL at +5.0 V)
- AN1503/D** – ECLinPS™ I/O SPICE Modeling Kit
- AN1504/D** – Metastability and the ECLinPS Family
- AN1568/D** – Interfacing Between LVDS and ECL
- AN1672/D** – The ECL Translator Guide
- AND8001/D** – Odd Number Counters Design
- AND8002/D** – Marking and Date Codes
- AND8020/D** – Termination of ECL Logic Devices
- AND8066/D** – Interfacing with ECLinPS
- AND8090/D** – AC Characteristics of ECL Devices

# MC10E141, MC100E141

## PACKAGE DIMENSIONS

PLCC-28  
FN SUFFIX  
PLASTIC PLCC PACKAGE  
CASE 776-02  
ISSUE E



### NOTES:

1. DATUMS -L-, -M-, AND -N- DETERMINED WHERE TOP OF LEAD SHOULDER EXITS PLASTIC BODY AT MOLD PARTING LINE.
2. DIMENSION G1, TRUE POSITION TO BE MEASURED AT DATUM -T-, SEATING PLANE.
3. DIMENSIONS R AND U DO NOT INCLUDE MOLD FLASH. ALLOWABLE MOLD FLASH IS 0.010 (0.250) PER SIDE.
4. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
5. CONTROLLING DIMENSION: INCH.
6. THE PACKAGE TOP MAY BE SMALLER THAN THE PACKAGE BOTTOM BY UP TO 0.012 (0.300). DIMENSIONS R AND U ARE DETERMINED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
7. DIMENSION H DOES NOT INCLUDE DAMBAR PROTRUSION OR INTRUSION. THE DAMBAR PROTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE GREATER THAN 0.037 (0.940). THE DAMBAR INTRUSION(S) SHALL NOT CAUSE THE H DIMENSION TO BE SMALLER THAN 0.025 (0.635).

| DIM | INCHES    |       | MILLIMETERS |       |
|-----|-----------|-------|-------------|-------|
|     | MIN       | MAX   | MIN         | MAX   |
| A   | 0.485     | 0.495 | 12.32       | 12.57 |
| B   | 0.485     | 0.495 | 12.32       | 12.57 |
| C   | 0.165     | 0.180 | 4.20        | 4.57  |
| E   | 0.090     | 0.110 | 2.29        | 2.79  |
| F   | 0.013     | 0.019 | 0.33        | 0.48  |
| G   | 0.050 BSC |       | 1.27 BSC    |       |
| H   | 0.026     | 0.032 | 0.66        | 0.81  |
| J   | 0.020     | ---   | 0.51        | ---   |
| K   | 0.025     | ---   | 0.64        | ---   |
| R   | 0.450     | 0.456 | 11.43       | 11.58 |
| U   | 0.450     | 0.456 | 11.43       | 11.58 |
| V   | 0.042     | 0.048 | 1.07        | 1.21  |
| W   | 0.042     | 0.048 | 1.07        | 1.21  |
| X   | 0.042     | 0.056 | 1.07        | 1.42  |
| Y   | ---       | 0.020 | ---         | 0.50  |
| Z   | 2°        | 10°   | 2°          | 10°   |
| G1  | 0.410     | 0.430 | 10.42       | 10.92 |
| K1  | 0.040     | ---   | 1.02        | ---   |

# MC10E141, MC100E141

ECLinPS is a trademark of Semiconductor Components Industries, LLC (SCILLC).

**ON Semiconductor** and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada

**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910

**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)

**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local  
Sales Representative

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ON Semiconductor:](#)

[MC100E141FN](#) [MC100E141FNG](#) [MC100E141FNR2](#)