

Technical drawing of a probe with dimensions in inches and millimeters.

Top View Dimensions:

- Overall Length: "B"
- Probe Tip Width: 0.34 [8.6]
- Probe Tip Diameter: 0.156 (3.96) DIA. HOLE REF.
- Probe Body Diameter: 0.06 (1.5) REF.
- Probe Body Length: "A"
- Probe Body Width: 0.40 [10.2]
- Probe Head Width: 0.56 [14.2]

Bottom View Dimensions:

- Overall Length: REF.
- Probe Tip Width: 0.22 [5.6]
- Probe Body Diameter: 0.13 DIA. [3.3]
- Probe Head Width: REF.

Additional Dimensions:

- Probe Head Diameter: 0.187 (4.75) TO 0.192 (4.88) DIA. HOLE REF.
- Probe Head Thickness: 0.03 (0.76) TO 0.08 (2.03) REF.

PANDUIT PART NO. *	"A" in/mm	"B" in/mm	WEIGHT lbs/100 (g)/pcs
CBLS18	0.18 (4.6)	0.92 (23.4)	0.024 (11)
CBLS25	0.25 (6.4)	0.98 (24.9)	0.051 (23)
CBLS37	0.37 (9.4)	1.11 (28.2)	0.075 (34)
CBLS50	0.50 (12.7)	1.23 (31.2)	0.099 (45)
CBLS62	0.62 (15.7)	1.35 (34.3)	0.123 (56)
CBLS75	0.75 (19.1)	1.48 (37.6)	0.150 (68)

* SEE CURRENT PRICE SHEET FOR PART
NUMBER SUFFIX, DESIGNATION FOR
PACKAGE SIZE AND PART COLOR.

[illegible]

PANDUIT

CORP. TINLEY PARK, ILLINOIS

CBL5

CIRCUIT BOARD LOCKING SUPPORT

UNLESS OTHERWISE SPECIFIED,
DIMENSIONAL TOLERANCES ARE:
(.X) ± 0.1 (2.5) (.XXX) ± 0.020 (.5)
(.XX) ± 0.05 (1.3) ANGLES $\pm 5^\circ$

UNLESS OTHERWISE SPECIFIED,
ALL DIMENSIONS ARE GIVEN
IN INCHES, THIRD ANGLE PROJECTION.

MAT'L:

NYLON 6/6

2X

DRAWING NO.

GB0239HL

DWG
A
SIZE

R	6-13-01	LGG		CHANGED DRAWING FROM SS-18657 (RV 4)	GB0239HL	R				
REV	DATE	BY	CHK	DESCRIPTION	ECN	- R	CUST	SUP		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Panduit:

[CBLS50-M](#) [CBLS75-M](#) [CBLS37-M](#) [CBLS18-M](#) [CBLS62-M](#) [CBLS25-M](#)