





CRYSTEK
CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CCHD-575 Model
5×7.5 mm SMD, 3.3V, HCMOS



CCHD-575

Ultra-Low Phase Noise Oscillator



Model CCHD-575 is the industry's lowest jitter clock oscillator in a 5×7.5 mm package. It features a typical phase jitter of 82fs RMS at 100 MHz. Close-in phase noise is -90 dBc/Hz @ 10 Hz while its floor is at -168 dBc/Hz. This oscillator may be small in size but it packs a punch inside. Its output driver is capable of driving ±24mA. This translates to a rise/fall time of ~600ps at 100 MHz with a 15pF load.

Applications include
DACs
ADCs
Low Phase Signal Sources
Test and Measurement

Rev: V
Date: 29-Jun-2020
Page 1 of 5



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM



CRYSTEK
CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CCHD-575

Ultra-Low Phase Noise Oscillator



CCHD-575 Model
5×7.5 mm SMD, 3.3V, HCMOS




Frequency Range: 12 MHz to 125 MHz*
Temperature Range: 0°C to +70°C
 (Option M) -20°C to +70°C
 (Option X) -40°C to +85°C
Storage: -45°C to 90°C
Input Voltage: 3.3V ±0.3V
Input Current: 15mA Typical, 25mA Max
Output: HCMOS
 Symmetry: 45/55% Max @ 50% Vdd
 Rise/Fall Time: 2ns Max @ 20% to 80% Vdd
 Logic: "0" = 10% Vdd Max
 "1" = 90% Vdd Min
 Load: 15pF
 Output Current: ±24mA Max
 82fs RMS Typical @ 100 MHz
 See plot
 -168 dBc/Hz Typical, -165 dBc/Hz Max
 None
 <3ppm 1st year, <1ppm thereafter




CCHD-575 Options:
Temperature Range: 0°C to +70°C (±20ppm, ±25ppm, ±50ppm)
 -20°C to +70°C (±25ppm, ±50ppm)
 -40°C to +85°C (±25ppm, ±50ppm)

Part Number Example:
 CCHD-575X-25-100.000 = 3.3V, 45/55, -40°C to +85°C (±25ppm), 100 MHz


RECOMMENDED REFLOW SOLDERING PROFILE



Denotes pad 1



SUGGESTED PAD LAYOUT



*Standard Frequencies (MHz)

12.000	48.000
16.924400	49.152
22.579200	50.000
24.000	54.000
24.576	80.000
27.000	100.000
40.000	125.000
45.158400	

Pad	Connection
1	NC
2	GND
3	Output
4	Vdd

PAD FINISH: Immersion Gold (ENIG); 5 micro inches maximum

Rev: V
 Date: 29-Jun-2020
 Page 2 of 5

Crystek Corporation reserves the right to make changes to its products and/or information contained herein without notice.
 No liability is assumed as a result of its use or application.





12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
 PHONE: 239-561-3311 • 800-237-3061
 FAX: 239-561-1025 • WWW.CRYSTEK.COM



CRYSTEK
CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CCHD-575 Model
5×7.5 mm SMD, 3.3V, HCMOS

CCHD-575 Ultra-Low Phase Noise Oscillator



Rev: V
Date: 29-Jun-2020
Page 3 of 5



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM





CRYSTEK
CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CCHD-575 Model
5×7.5 mm SMD, 3.3V, HCMOS

CCHD-575

Ultra-Low Phase Noise Oscillator



Rev: V
Date: 29-Jun-2020
Page 4 of 5



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM




CRYSTEK
CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CCHD-575 Model
5×7.5 mm SMD, 3.3V, HCMOS

CCHD-575

Ultra-Low Phase Noise Oscillator



Rev: V
Date: 29-Jun-2020
Page 5 of 5



CRYSTEK
CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FLORIDA 33913
PHONE: 239-561-3311 • 800-237-3061
FAX: 239-561-1025 • WWW.CRYSTEK.COM

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Crystek:](#)

[CCHD-575-50-100.000](#) [CCHD-575-50-80.000](#) [CCHD-575-25-22.5792](#) [CCHD-575-25-24.576](#) [CCHD-575X-25-100.000](#) [CCHD-575-25-24.000](#) [CCHD-575X-25-125.000](#)