


## LOW-NOISE DUAL OPERATIONAL AMPLIFIER

### ■ GENERAL DESCRIPTION


The NJM5532 is a high performance dual low noise operational amplifier. Compared to the standard dual operational amplifiers, such as the NJM4558, it shows better noise performance, improved output drive capability, and considerably higher small-signal and power bandwidths. It is compensated internally for voltage follower circuit. This makes the device especially suitable for application in high quality and professional audio equipment, instrumentation, control circuits, and telephone channel amplifiers.

If very low noise characteristic is of prime importance, it is recommended D-Rank type products (NJM5532DD/LD/MD). These have specified maximum limits for equivalent input noise voltage.

### ■ PACKAGE OUTLINE



NJM5532D  
(DIP8)



NJM5532L  
(SIP8)





NJM5532M  
(DMP8)

### ■ FEATURES

- Operating Voltage  $\pm 3V \sim \pm 22V$
- Small Signal Bandwidth 10MHz typ.
- Output Drive Capability 600 $\Omega$ , 10Vrms typ.
- Input Noise Voltage 5nV/ $\sqrt{\text{Hz}}$  typ.
- Power Bandwidth 140kHz typ.
- Slew Rate 8V/ $\mu\text{s}$  typ.
- Bipolar Technology
- Package Outline DIP8, DMP8, SIP8


### ■ PIN CONFIGURATION



#### PIN FUNCTION

- 1.A OUTPUT
- 2.A -INPUT
- 3.A +INPUT
- 4.V<sup>-</sup>
- 5.B +INPUT
- 6.B -INPUT
- 7.B OUTPUT
- 8.V<sup>+</sup>

### ■ EQUIVALENT CIRCUIT ( 1/2 Shown )



## ■ ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Supply Voltage	$V^+ / V^-$	$\pm 22$	V
Common Mode Input Voltage Range	$V_{ICM}$	$V^+ / V^-$	V
Differential Input Voltage Range	$V_{ID}$	$\pm 0.5$	V
Power Dissipation	$P_D$	DIP8 : 500 DMP8 : 600(Note1) SIP8 : 800	mW
Operating Temperature Range	$T_{opr}$	-20~+75	°C
Storage Temperature Range	$T_{stg}$	-40~+125	°C

(Note1) On the cermic PCB (10x20x0.635mm)

## ■ RECOMMENDED OPERATING VOLTAGE (Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Supply Voltage	$V^+ / V^-$	$\pm 3 \sim \pm 22$	V

## ■ ELECTRICAL CHARACTERISTICS ( $V^+ / V^- = \pm 15V$ , Ta=25°C, unless otherwise noted.)

### ● DC ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Input Offset Voltage	$V_{IO}$	$R_S \leq 10k\Omega$	-	0.5	4	mV
Input Offset Current	$I_{IO}$		-	10	150	nA
Input Bias Current	$I_B$		-	200	800	nA
Supply Current	$I_{CC}$	$R_L = \infty$	-	9	16	mA
Common Mode Input Voltage Range	$V_{ICM}$		$\pm 12$	$\pm 13$	-	V
Common Mode Rejection Ratio	CMR	$R_S \leq 10k\Omega$	70	100	-	dB
Supply Voltage Rejection Ratio	SVR	$R_S \leq 10k\Omega$	80	100	-	dB
Voltage Gain1	$A_{V1}$	$R_L \geq 2k\Omega$ , $V_O = \pm 10V$	88	100	-	dB
Voltage Gain2	$A_{V2}$	$R_L \geq 600\Omega$ , $V_O = \pm 10V$	83.5	94	-	dB
Maximum Output Voltage1	$V_{OM1}$	$R_L \geq 600\Omega$	$\pm 12$	$\pm 13$	-	V
Maximum Output Voltage2	$V_{OM2}$	$R_L \geq 600\Omega$ , $V^+ / V^- = \pm 18V$	$\pm 15$	$\pm 16$	-	V
Input Resistance	$R_{IN}$		30	300	-	kΩ
Short Circuit Output Current	$I_{OS}$		-	38	-	mA

### ● AC ELECTRICAL CHARACTERISTICS







PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Resistance	$R_O$	$A_V = 30dB$ , $f = 10kHz$ , $R_L = 600\Omega$	-	0.3	-	Ω
Overshoot		$A_V = 1$ , $V_{IN} = 100mV_{PP}$ , $R_L = 100pF$ , $R_L = 600\Omega$	-	10	-	%
Voltage Gain	$A_V$	$f = 10kHz$	-	67	-	dB
Slew Rate	SR		-	8	-	V/μs
Gain Bandwidth Product	GB	$C_L = 100pF$ , $R_L = 600\Omega$	-	10	-	MHz
Power Bandwidth	$W_{PG}$	$V_O = \pm 10V$	-	140	-	kHz
	$W_{PG}$	$V_O = \pm 14V$ , $R_L = 600\Omega$ , $V^+ / V^- = \pm 18V$	-	100	-	kHz
Equivalent Input Noise Voltage	$e_n$	$f_O = 30Hz$	-	8	-	nV/√Hz
	$e_n$	$f_O = 1kHz$	-	5	-	nV/√Hz
Equivalent Input Noise Current	$i_n$	$f_O = 30Hz$	-	2.7	-	pA/√Hz
	$i_n$	$f_O = 1kHz$	-	0.7	-	pA/√Hz
Channel Separation	CS	$f = 1kHz$ , $R_S = 5k\Omega$	-	110	-	dB

## ■ ELECTRICAL CHARACTERISTICS (D-ranktype(Note2), $V^+ / V^- = \pm 15V$ , Ta=25°C, unless otherwise noted.)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Equivalent Input Noise Voltage	$V_{NI}$	RIAA, $R_S = 2.2k\Omega$	-	-	1.4	μVrms


(Note2) D-rank type is a Equivalent Input Noise Voltage selected product.

## TYPICAL CHARACTERISTICS




## ■ TYPICAL CHARACTERISTICS


Supply Current vs. Supply Voltage  
 $T_a=25^\circ\text{C}$




Supply Current vs. Temperature  
 $V^+/V^-=\pm 15\text{V}$




Input Offset Voltage vs. Temperature  
 $V^+/V^-=\pm 15\text{V}$




Input Bias Current vs. Temperature  
 $V^+/V^-=\pm 15\text{V}$



Maximum Output Voltage vs. Supply Voltage  
 $R_L=2\text{k}\Omega$ ,  $T_a=25^\circ\text{C}$




Maximum Output Voltage vs. Temperature  
 $V^+/V^-=\pm 15\text{V}$ ,  $R_L=600\Omega$




## ■ TEST CIRCUIT

Noise Voltage (RIAA) measurement circuit



## ■ NOTICE

When used in voltage follower circuit, put a current limit resistor into non-inverting input terminal in order to avoid inside input diode destruction when the power supply is turned on. ( ref.Fig.1 )




(Fig.1)

## ■ Caution to Thermal Design

If the NJM5532 junction temperature ( $T_j$ ) exceeds guaranteed value (125 degree) or the package power dissipation ( $P_D$ ), there is possibility of the NJM5532 deterioration or breakdown.

The NJM5532 supply current is higher ( $I_{CCMAX}=16mA$  at  $V^+/V^-=\pm 15V, T_a=+25^\circ C$ ) and has positive temperature coefficient (Refer to Supply Current vs. Temperature characteristic).

Therefore, you should carefully design with due attention to the supply voltage, the internal power dissipation and the ambient temperature.



## ■ Countermeasure to Excess Current by Parasitic Circuit

When the NJM5532  $V^+$  is open (Fig.2), the NJM5532 may be burnt flowing the excess current by internal parasitic circuit(Fig.3).The excess current generating condition is following:

- / Between input terminal and  $V^-$  voltage difference is higher.
- / Input terminal has no resistance of  $1k\Omega$  or more.
- /  $V^+$  terminal is connected with low impedance. (Ietc is higher)




Fig.2




Fig.3

For countermeasure to excess current by parasitic circuit, NJRC recommends the following method.

- / prevent operating of a parasitic circuit by inserting a SBD (Fig.4-1/4-2).
- / limiting a parasitic circuit operation by inserting a resistance ( $1k\Omega$  or more) (Fig.5).




Fig.4-1




Fig.4-2




Fig.5

[CAUTION]  
The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[NJR:](#)

[NJM5532D](#) [NJM5532M](#) [NJM5532L](#) [NJM5532M-TE2](#) [NJM5532M-TE3](#) [NJM5532DD](#) [NJM5532MD](#) [NJM5532MD-TE2](#) [NJM5532MD-TE1](#) [NJM5532MD-TE3](#) [NJM5532MTE1 \(REEL 2000 PCS\)](#) [NJM5532M-TE1](#)